

product data sheet

VARCUT 4220

Dual Purpose extreme pressure cutting oil

Varcut 4220 is an extreme pressure oil developed for use on medium tensile steels and all nonferrous metals in a wide range of machinery.

Varcut 4220 contains inactive sulphur EP and lubricity additives together with antimist and anti-oxidant packages

Varcut 4220 is suitable for use as a lubricating oil where a viscosity grade of ISO 22 is required. It can be utilized in automatic lathes where cross leakage into gearboxes can occur.

Features & Benefits

- EP and lubricity additives
- Anti-misting formulation
- Light colour
- Formulated on high quality mineral oil
- Multipurpose oil
- Can be used as a lubricating oil in certain machinery
- Medium viscosity oil

Varcut 4220	
Characteristic	Typical Data
Colour	Brown
Viscosity @40°C	22 mm ² /s
Sulphur	Yes – inactive
Ester	Yes
Specific Gravity @20°C	0.87

product data sheet

Operational Recommendations

Varcut 4220 is designed to be used as supplied.

Varcut 4220 is safe for use on most metals.

Varcut 4220 should always be stored indoors and protected from extremes of temperature.

Although this product is not classified as hazardous to health, good standards of hygiene and housekeeping should always be adopted when using any industrial oils.

A separate MSDS is available for this product. Additional advice can also be obtained from your local representative.

This publication contains information and recommendations based upon data obtained from sources considered reliable and believed to be correct, however, no warranty or guarantee is expressed or implied