

## TOROTEC 5W-30 PSA

**Product Code:** PCM029 | **Revision:** 20220907



Fully synthetic & mid SAPS automotive engine oil, ACEA C2.

### Available Pack Sizes



### Applications

A fully synthetic and mid SAPS engine oil formulated for use with petrol and diesel engines, particularly Peugeot & Citroen vehicles. Our specialist Adaptive Molecular Technology maintains engine power and optimum efficiency to improve overall reliability whilst supporting exhaust after-treatment devices throughout the vehicle's lifecycle.

Recommended by Aztec Oils as suitable for the following applications

ACEA C2  
API SN/CF  
Peugeot/Citroen B71 2290  
Suitable for Fiat

### Benefits

- Advanced anti-wear technology helps to protect engine components.
- Engineered to have good oxidation resistance and thermal stability.
- Excellent high and low temperature performance.
- High standards of engine cleanliness.
- Increased fuel efficiency.
- Maintains performance over extended service intervals.

### Typical Test Data

Density @ 15°C (kg/m <sup>3</sup> )	ASTM D4052	0.846
Flash Point (°C)	ASTM D92	212
Kinematic Viscosity @ 40°C (mm <sup>2</sup> /s)	ASTM D445	75
Kinematic Viscosity @ 100°C (mm <sup>2</sup> /s)	ASTM D445	12.2
Pour Point (°C)	ASTM D97	-45
Total Base Number (mg KOH/g)	ASTM D2896	7.8
Viscosity Index	ASTM D2207	160

### Health, Safety & Recommendations

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This lubricant, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is given in good faith, but without warranty.

### Health, Safety & Recommendations

- A Safety Data Sheet is available for consultation at [www.aztecoils.co.uk](http://www.aztecoils.co.uk).
- Before using this product, the vehicles maintenance guide should be checked and oil changes must be carried out in accordance with the manufacturers' recommendations.
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- When disposing of the product after use, please protect the environment and comply with local regulations.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This lubricant, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is given in good faith, but without warranty.