


TRANSMATEC TRANS-4 10W

Product Code: GTO026 | **Revision:** 20220526



Specialist mineral oil based fluid for hydraulics and transmission components.

Available Pack Sizes



Applications

A monograde fluid to meet the requirements of transmissions found in off-highway, construction and earthmoving equipment. Blended from quality base oils with performance additives these fluids are designed to provide improved frictional properties, anti-wear performance and oxidation stability leading to longer equipment life.

Recommended by Aztec Oils as suitable for the following applications

Allison C4
Caterpillar TO-4
Komatsu KES 07.868.1
ZF TE-ML 03C

Benefits

- Excellent sludge control.
- Good long-term anti-wear protection.
- Good seal compatibility.
- Longer equipment life.
- Improved friction properties for use with oil immersed frictional disks.
- Suitable for a wide range of off-highway equipment.

Typical Test Data

| | | |
|--|------------|------|
| Density @ 15°C (kg/m ³) | ASTM D4052 | 0.86 |
| Flash Point (°C) | ASTM D92 | >190 |
| Kinematic Viscosity @ 40°C (mm ² /s) | ASTM D445 | 46.9 |
| Kinematic Viscosity @ 100°C (mm ² /s) | ASTM D445 | 6.9 |
| Pour Point (°C) | ASTM D97 | <-30 |
| Viscosity Index | ASTM D2207 | 102 |

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

Recommendations

- A Safety Data Sheet is available for consultation at www.aztecoils.co.uk.
- Before using this product, the vehicles maintenance guide should be checked and oil changes must be carried out in accordance with the manufacturers' recommendations.
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- Not to be used as an engine lubricant.
- When disposing of the product after use, please protect the environment and comply with local regulations.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This lubricant, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is given in good faith, but without warranty.



In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This lubricant, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is given in good faith, but without warranty.