

TRANSMATEC SS-5 75W-80

Product Code: GTO021 | **Revision:** 20220719



Semi synthetic high-performance transmission oil.

Available Pack Sizes



Applications

A semi synthetic high-performance automotive gear oil with purpose designed additive technology to provide a long service life. It offers higher levels of performance when compared to straight mineral oils whilst remaining fully compatible with mineral oils, enabling it to be simply used as a replacement product on a drain and fill basis.

Recommended by Aztec Oils as suitable for the following applications

API GL-5
ZF TE-ML 02B

Not suitable for copper containing synchronizers.

Benefits

- Compatible with most elastomers and seal materials.
- Good oxidation stability to provide resistance to aging.
- Exceptional anti-wear protection.
- Long service life.
- Superb protection against rust and corrosion.

Typical Test Data

Density @ 15°C (kg/m ³)	ASTM D4052	0.86
Flash Point (°C)	ASTM D92	>190
Kinematic Viscosity @ 40°C (mm ² /s)	ASTM D445	55
Kinematic Viscosity @ 100°C (mm ² /s)	ASTM D445	9.7
Pour Point (°C)	ASTM D97	<-35
Viscosity Index	ASTM D2207	163

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

Recommendations

- A Safety Data Sheet is available for consultation at www.aztecoils.co.uk.
- Before using this product, the vehicles maintenance guide should be checked and oil changes must be carried out in accordance with the manufacturers' recommendations.
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- When disposing of the product after use, please protect the environment and comply with local regulations.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This lubricant, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is given in good faith, but without warranty.