

# SYNTHETIC 5W/30 C2/C3



**PRODUCT DESCRIPTION**

Synthetic 5w/30 is innovative, versatile, all-synthetic ester-containing premium synthetic engine oil for modern diesel and gas turbocharged and non-turbocharged engines.

Designed in accordance with the requirements of European automakers see specifications below:

Classifications

SAE	5W-30	ACEA	C3, C2	API	SN/CH-4
-----	-------	------	--------	-----	---------

Manufacturer

BMW LL-04	GM dexos2
MB 226.5, 229.31, 229.51, 229.52	RENAULT RN0700, RN0710
VOLKSWAGEN 505 01	

**Product Properties**

- High fuel efficiency due to optimal antifricition properties;
- Highly effective additive package and synthetic base provide confident cold start in any conditions, thereby significantly reducing engine starting wear;
- Due to its excellent washing and dispersing properties and the highest thermal oxidative stability, it effectively fights against all types of deposits and keeps engine parts clean throughout the entire interval between replacements;
- The presence of ester components in combination with optimal viscosity-temperature characteristics guarantees the highest strength of the oil film, which provides excellent anti-wear properties which, combined with excellent pump ability, significantly increase engine life even in the most severe operating conditions;
- Compatible with all exhaust gas after treatment systems;
- Suitable for engines using liquefied natural gas (LNG) and liquefied petroleum (LPG) gas;
- It is applied in engines with the extended interval of replacement of oil (Long Life) to 40 000 km and ordinary.

Designed for gasoline and diesel engines in a wide fleet of cars, light SUVs, minibuses and light trucks of European and other manufacturers, where the performance level of ACEA C3 is required.

Due to its versatility, it is especially recommended for taxi fleets.

The oil is not suitable for use in heavy trucks and similar vehicles!

# TECHNICAL DATA SHEET

## TYPICAL PROPERTIES

### General Information

· Physical state:	Fluid
· Colour:	Yellow-brown
· Melting point/freezing point:	-42 °C
· Boiling point	>350 °C
· Flash point:	>216 °C
· Kinematic viscosity at 40 °C	>65 mm <sup>2</sup> /s
· Density at 20 °C:	0.85 g/cm <sup>3</sup>

## PACK SIZES

BULK, 1000LTR IBC, 205LTR, 25LTR, 20LTR, 5LTR