

TOROTEC PERFORMANCE 10W-30

Product Code: PCM005 | **Revision:** 20240819



Robust mineral automotive engine oil, ACEA A3/B4.

Available Pack Sizes



Applications

A multigrade engine oil manufactured from carefully selected, high quality mineral base oils and incorporating advanced Adaptive Molecular Technology. The inclusion of enhanced dispersant additives helps to maintain engine cleanliness in petrol and diesel engines, whilst having superior detergency performance to control and reduce the formation of unwanted deposits to prevent the creation of hard lacquers in turbo chargers, piston rings and the valve train.

Recommended by Aztec Oils as suitable for the following applications

ACEA A3/B3, A3/B4
API SL/CH-4
Mercedes-Benz 229.1/229.3

Benefits

- Advanced anti-wear technology helps to protect engine components.
- Excellent protection against oxidation.
- High shear stability for stay in grade performance.
- Reduces corrosion, varnish and the agglomeration of sludge.
- Superb thermal stability at high temperatures.

Typical Test Data

Density @ 15°C (kg/m ³)	ASTM D4052	0.866
Flash Point (°C)	ASTM D92	212
Kinematic Viscosity @ 40°C (mm ² /s)	ASTM D445	70.5
Kinematic Viscosity @ 100°C (mm ² /s)	ASTM D445	11
Pour Point (°C)	ASTM D97	-35
Total Base Number (mg KOH/g)	ASTM D2896	10.2
Viscosity Index	ASTM D2207	147

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

Health, Safety & Recommendations

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.

Health, Safety & Recommendations

- A Safety Data Sheet is available for consultation at www.aztecoils.co.uk.
- Before using this product, the vehicles maintenance guide should be checked and oil changes must be carried out in accordance with the manufacturers' recommendations.
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- When disposing of the product after use, please protect the environment and comply with local regulations.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.