



PETRONAS

TECHNICAL CHARACTERISTICS

TUTELA TRANSMISSION STARGEAR FV

PRODUCT CODE: 2287

APPLICATION

Synchronized manual transmissions Lubricant suited to gearboxes fitted to the Volkswagen group vehicles.

SPECIFICATIONS

SAE 75W-90, API GL 4, VW 501.50 Performance

TEST DESCRIPTION

TEST DESCRIPTION	METHOD	UNIT	TYPICAL VALUE
ASPECT	--	--	B&C
COLOUR	ASTM D 1500	--	L1
DENSITY 15°C	ASTM D 4052	g/cm ³	0.890
VISCOSITY @ 100°C	ASTM D 445	cSt	14.5
VISCOSITY @ 40°C	ASTM D 445	cSt	86
VISCOSITY INDEX	ASTM D 2270	--	172
VISCOSITY @ -40°C	ASTM D 2983	cPs	130000
POUR POINT	ASTM D 97	°C	-42
FLASH POINT Cl. O. C.	ASTM D 92	°C	>170
COPPER CORROSION (3h/100°C)	ASTM D 130	--	1A
FOAM @ 24°C	ASTM D 892	cc/s	tr/0

All technical data is provided for reference only.

RESEARCH & DEVELOPMENT

05/2016