

HYDRATEC SYN CHF

Product Code: MAI004 | **Revision:** 20240821



Synthetic central hydraulic fluid.

Available Pack Sizes



Applications

A carefully formulated synthetic fluid designed to provide high performance in a wide range of operating conditions to a variety of essential automotive systems including power steering, self-levelling hydropneumatic suspension, shock absorbers, traction and stability control, hydraulics for convertible tops and central locking systems.

Recommended by Aztec Oils as suitable for the following applications

BMW 81 22 9 407 758
ISO 7308
MAN 3623/93
Mercedes-Benz 345.0
Opel B040.0070
Porsche 000.043.203.33

Benefits

- Exceptionally high viscosity index to give performance over a wide temperature range.
- Excellent corrosion resistance.
- Outstanding anti-wear & anti-oxidant properties.
- Provides excellent lubricity.
- Superb hydrolytic stability.

Typical Test Data

Appearance		Clear & bright, green fluid
Density @ 15°C (kg/m ³)	ASTM D4052	0.835
Flash Point (°C)	ASTM D92	>130
Kinematic Viscosity @ 40°C (mm ² /s)	ASTM D445	18.7
Kinematic Viscosity @ 100°C (mm ² /s)	ASTM D445	6
Operating Temperatures Range		-40°C to 130°C
Pour Point (°C)	ASTM D97	<-50
Viscosity Index	ASTM D2207	310

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

Health, Safety & Recommendations

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.

Health, Safety & Recommendations

- A Safety Data Sheet is available for consultation at www.aztecoils.co.uk.
- Before using the product, it is advised to consult the vehicle handbook for the correct fluid type.
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- Never use this fluid in reservoirs painted black and those systems using vegetable or synthetic based fluids.
- Not miscible or compatible with synthetic fluids including DOT 3, DOT 4, DOT 5, DOT 5.1 and former Citroen fluids.
- When disposing of the product after use, please protect the environment and comply with local regulations.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.