

SLIDEWAY OILS



PRODUCT DESCRIPTION

Premium quality lubricating, machine oil with added tacky, anti-lifting additives for the lubrication of slides on machine tools. The tackifier improves adhesion and prevents the oil from being squeezed off the slideways. It also helps prevent the oil from being washed away by the cutting fluids.

APPLICATIONS

Use for lubrication of slideways where, stick-slip-free performance is required or where a tacky adhesive lubricant is required.

BENEFITS

- Excellent filterability
- Thermally stable
- Good oxidation resistance
- Wide temperature range usage
- Good corrosion protection
- Excellent demulsibility

TYPICAL TEST DATA

Grade	-	32	68	150	220
Specific Gravity	-	0.873	0.882	0.890	0.898
Kinematic Visc @ 100°C	-	5.4	8.8	17.8	20
Kinematic Visc @ 40°C	-	32.0	68.0	150.0	220.0
Viscosity Index (VI)	-	95	95	100	100
Pour Point °C	-	-20	-20	-15	-15
Flash point °C	-	215	220	230	230

TECHNICAL DATA SHEET

PACK SIZES

Slideway Oil is packed in the following sizes:-

5 Litre, 20 Litre, 25 Litre, 205 Litre, 1000 Litre IBC, Bulk Pump Off.

For Health and safety information please refer to the relevant health and safety data sheet.

The content of this data sheet is given in good faith but without warranty.